

Date:14-11-2016

No.006/P.M.S/T.P/16

Technical Publications

Pages - (31)

Service Suppliers

P.M.S / Procedure for the approval

Content:-

- General
- Objective
- Definitions

Part A - Approval Process

- 1- Application
- 2- Procedure for Approval and Certification
- 3- Certification
- 4- Information Regarding Alterations to the Certified Service Operating System
- 5- Cancellation of Approval
- 6- Existing Approvals

Part B - Special Requirements

- 1- Firms engaged in thickness measurements on ships.
- 2- Firms engaged in tightness testing of closing appliances such as hatches, doors, etc. with ultrasonic equipment.
- 3- Firms carrying out in-water survey of ships and mobile offshore units.
- 4- Firms engaged in inspection and maintenance of fire extinguishing equipment and system.
- 5- Firms engaged in servicing inflatable liferafts, inflatable lifejackets, hydrostatic release units, inflatable rescue boats, marine evacuation systems.
- 6- Firms engaged in inspections and testing of radio communication equipment.
- 7- Firms engaged in inspections and maintenance of self-contained breathing apparatus.
- 8- Firms engaged in examination of Ro-Ro ship's bow, stern, side and inner doors.
- 9- Firms engaged in annual performance testing of Voyage Data Recorders (VDR) and simplified Voyage Data Recorders (S-VDR).
- 10- Firms engaged in inspections of low location lighting systems using photo luminescent materials and evacuation guidance systems used as an alternative to low location lighting systems.
- 11- Firms engaged in sound pressure level measurements of public address and general alarm systems on board ships.
- 12- Firms engaged in testing of coating systems in accordance with IMO Resolution MSC.215(82) as amended and IACS UI SC223 and/or MSC.288(87) as amended.
- 13- Firms engaged in the servicing and maintenance of lifeboats, launching appliances, on load release gear and davit-launched liferaft automatic release hooks.
- 14- Firms engaged in measurements of Noise level Onboard Ships.
- 15- Firms engaged in tightness testing of primary and secondary barriers of gas carriers with membrane cargo containment systems for vessels in service.



GENERAL /

For the requirements of approval of firms providing services, such as measurements, tests or maintenance of safety systems and equipment, **P.M.S** applies the procedure as described in Parts A and B of this publication.

OBJECTIVE /

To set minimum requirements for the approval and certification of service suppliers that is applicable to both initial and renewal audits.

DEFINITIONS /

Manufacturer	A company that manufactures equipment required to be periodically serviced and/or maintained.
	A person or company, not employed by P.M.S, who at the request of an equipment manufacturer,
Service Supplier	shipyard, vessel's owner or other client acts in connection with inspection work and provides services
••	for a ship or a mobile offshore drilling unit such as measurements, tests or maintenance of safety
	systems and equipment, the results of which are used by surveyors in making decisions affecting
	classification or statutory certification and services.
Agent	A Person or Company authorised to act for or to represent a Manufacturer or approved/recognized
	service supplier.
Subsidiary	A Company partly or wholly owned by a Manufacturer or approved/recognized service supplier.
Subcontractor	A Person or Company providing services to a Manufacturer or approved/recognized service supplier,
	with a formal contract defining the assumption of the obligations of the service supplier.



For further information, please refer to PMS on Website of (www.pmsclass.org) - https://pmsclass.org/rules/pms-technical-publications/



PART A /

> APPROVAL PROCESS

1- APPLICATION /

This publication applies to the approval of the following categories of service suppliers.

Statutory services for firms engaged in:

- > Servicing inflatable life rafts, inflatable life jackets, hydrostatic release units, inflatable rescue boats, marine evacuation systems.
- Inspections and testing of radio communication equipment.
- > Inspections and maintenance of self-contained breathing apparatus.
- Annual performance testing of Voyage Data Recorders (VDR) and simplified Voyage Data Recorders (S-VDR)
- > Sound pressure level measurements of public address and general alarm systems on board ships.
- > Inspections of low location lighting systems using photo luminescent materials and evacuation guidance systems used as an alternative to low-location lighting systems
- > Servicing and maintenance of lifeboats, launching appliances, on load release gear and davit-launched liferaft automatic release hooks
- > Inspection, performance testing and maintenance of Automatic Identification Systems (AIS)

Classification and/or Statutory services for firms engaged in:

- > Servicing thickness measurements on ships except non-ESP ships less than 500 gross tonnage and all fishing vessels.
- > Carrying out in-water survey of ships and mobile offshore units
- > Inspections and maintenance of fire extinguishing equipment and systems
- > Tightness testing of closing appliances such as hatches, doors etc. with ultrasonic equipment
- ➤ Measurements of noise level on board ships
- Examination of Ro-Ro ship's bow, stern, side and inner doors
- > Testing of coating systems in accordance with IMO Resolution MSC.215(82), as amended, and IACS UI SC223 and/or MSC.288(87), as amended.
- > Tightness testing of primary and secondary barriers of gas carriers with membrane cargo containment systems for vessels in service.

Where **P.M.S** accepts work of a third party (e.g., service supplier) approved by itself, **P.M.S** shall verify the performance of such services. For statutory service, the flag State may increase the scope of verification to be applied to these services. For the purpose of accountability to the flag State, the work performed by the third party (e.g., service supplier) constitutes the work of **P.M.S** and shall be subject to the requirements incumbent upon P.M.S under the RO Code IMO MSC.349 (92) and MEPC.237(65).

Where the results of the following service providers are used by a P.M.S Surveyor in making decisions affecting classification services then that service provider must be approved and verified by P.M.S:

- > Firms engaged in thickness measurements on ships except non-ESP ships less than 500 gross tonnage and all fishing vessels.
- Firms carrying out in-water survey of ships and mobile offshore units.
- Firms engaged in tightness testing of closing appliances such as hatches, doors etc. with ultrasonic equipment.



Where such services are used by **P.M.S** Surveyors in making decisions affecting statutory certification and service, the firms are subject to approval and verification by **P.M.S** where **P.M.S** is so authorised by the relevant flag Administration (i.e. the flag of the ship on which the servicing is to be done or the service equipment is to be used). For such services **P.M.S** may accept approvals done by :

- > the flag Administration itself;
- > duly authorized organizations acting on behalf of the flag Administration (such as IACS Classification Members); or
- by other organizations those are acceptable to the flag Administration (e.g. other governments, etc.).

Use of the approved service suppliers is not mandatory for the following services, unless instructed otherwise by the flag Administration with respect to statutory certification.

- Firms engaged in inspections of low location lighting systems using photo luminescent materials and evacuation guidance systems used as an alternative to low-location lighting systems.
- > Firms engaged in sound pressure level measurements of public address and general alarm systems on board ships.
- Firms engaged in measurements of noise level onboard ships.
- Firms engaged in testing of coating systems in accordance with IMO Resolution MSC.215(82) as amended and IACS UI SC223 and/or MSC.288(87) as amended.
- Firms engaged in examination of Ro-Ro ships bow, stern, side and inner doors.

Detailed requirements specific to the various categories of suppliers are given in Part B. National and/or international requirements may give additional requirements. References to such national and/or international requirements are given in Part B.

2- PROCEDURE FOR APPROVAL AND CERTIFICATION /

SUBMISSION OF DOCUMENTS.

The following documents are to be submitted to **P.M.S** for review (specific requirements as relevant are given in Part B):

- Outline of company, e.g. organization and management structure, including subsidiaries to be included in the approval/certification
- List of nominated agents, subsidiaries and subcontractors
- Experience of the company in the specific service area
- ➤ For categories of Service Suppliers that require authorization from manufacturers, manufacturer's documentary evidence that the Service Supplier has been authorized or licensed to service the particular makes and models of equipment for which approval is sought shall be provided.
- List of operators/technicians/inspectors documenting training and experience within the relevant service area, and qualifications according to recognized national, international or industry standards, as relevant
- Description of equipment used for the particular service for which approval is sought
- ➤ A guide for operators of such equipment
- > Training programmes for operators/technicians/inspectors
- > Check lists and record formats for recording results of the services referred to in Part B.
- > Quality Manual and/or documented procedures covering requirements in Quality System
- > Documented procedures for communication with the crew prior to commencing work, so that it is safe to decommission the equipment being maintained, and to provide a safe system of work in place.
- > Evidence of approval/acceptance by other bodies, if any.
- ➤ Information on the other activities which may present a conflict of interest
- > Record of customer claims and of corrective actions requested by certification bodies



GENERAL REQUIREMENTS.

Extent of Approval

The supplier shall demonstrate, as required by below given paragraphs, that it has the competence and control needed to perform the services for which approval is sought.

Training of personnel

The supplier is responsible for the qualification and training of its personnel to a recognized national, international or industry standard as applicable. Where such standards do not exist, the supplier is to define standards for the training and qualification of its personnel relevant to the functions each is authorised to perform. The personnel shall also have adequate experience and be familiar with the operation of any necessary equipment. Operators/technicians/inspectors shall have had a minimum of one year tutored on-the-job training. Where it is not possible to perform internal training, a program of external training may be considered as acceptable.

Supervision

The supplier shall provide supervision for all services provided. The responsible supervisor shall have had a minimum of two years of experience as an operator/technician/inspector within the activity for which the supplier is approved. For a supplier consisting of one person, that person shall meet the requirements of a supervisor.

Personnel records

The supplier shall keep records of the approved operators/technicians/inspectors. The record shall contain information on age, formal education, training and experience for the services for which they are approved.

Equipment and facilities.

The supplier shall have the necessary equipment and facilities for the service to be supplied. A record of the equipment used shall be kept and available. The record shall contain information on maintenance and results of calibration and verifications. **P.M.S** shall assess and record the validity of previous measuring results when the equipment is found not to conform to requirements. P.M.S shall take appropriate action on the equipment affected.

Control of data.

When computers are used for the acquisition, processing, recording, reporting, storage, measurement assessment and monitoring of data, the ability of computer software to satisfy the intended application shall be documented and confirmed by the service supplier. This shall be undertaken prior to initial use and reconfirmed as necessary.

Note:

Commercial off-the-shelf software (e.g. word processing, database and statistical programmes) in general use within their designed application range may be considered to be sufficiently validated and do not require any subsequent confirmation.

Where several servicing stations are owned by a given company, each station is to be assessed and approved except as specified in following paragraph "Auditing of the Supplier".

Procedures

The supplier shall have documented work procedures covering all services supplied.

Subcontractors

The supplier shall give information of agreements and arrangements if any parts of the services provided are subcontracted. Particular emphasis shall be given to quality management by the supplier in following-up such subcontracts. Subcontractors providing anything other than equipment shall also meet the requirements of paragraphs "General Requirements" and "Quality System" of this procedure.



Verification

The supplier shall verify that the services provided are carried out in accordance with approved procedures.

Reporting

The report shall be prepared in a form acceptable to P.M.S. The report should detail the results of inspections, measurements, tests, maintenance and/or repairs carried out. Special guidelines may be given in Part B. The report shall include a copy of the Certificate of Approval.

Documented procedures and instructions should be available for the recording of damages and defects found during inspection, servicing and repair work. This documentation is to be made available upon request.

AUDITING OF THE SUPPLIER.

Upon reviewing the submitted documents with satisfactory result, the supplier is audited in order to ascertain that the supplier is duly organised and managed in accordance with the submitted documents, and that it is considered capable of conducting the services for which approval/certification is sought.

CERTIFICATION.

Certification is conditional on a practical demonstration of the performance of the specific service as well as satisfactory reporting being carried out. At renewal audits, evidence of performance, verified by class surveyor, since the previous audit is sufficient to satisfy this requirement.

QUALITY SYSTEM

The supplier shall have a documented system covering at least the following:

- > code of conduct for the relevant activity
- > maintenance and calibration of equipment
- training programmes for operators/technicians/inspectors
- > supervision and verification to ensure compliance with operational procedures
- > recording and reporting of information
- quality management of subsidiaries, agents and subcontractors
- > job preparation
- periodic review of work process procedures, complaints, corrective actions, and issuance, maintenance and control of documents.

A documented Quality system complying with the most current version of ISO 9000 series and including the above items, would be considered acceptable.

If a manufacturer of equipment (and/or its service supplier) applies to **P.M.S** for inclusion of its nominated agents and/or subsidiaries in the approval, then it must have implemented a quality system certified in accordance with the most current version of ISO 9000 series. The quality system must contain effective controls of the manufacturer's (and/or service supplier's) agents and/or subsidiaries. The nominated agents/subsidiaries must also have in place an equally effective quality system complying with the most current version of ISO 9000 series. Such approvals shall be based upon an evaluation of the quality system implemented by the parent company against the most current version of ISO 9000 series. **P.M.S** may require follow-up audits on such agents or subsidiaries against the most current version of ISO 9000 series to confirm adherence to this quality system.



RELATIONS WITH THE EQUIPMENT MANUFACTURER.

A company which works as a service station for manufacturer(s) of equipment (and as a service supplier in this field), shall be assessed by the manufacturer(s) and nominated as their agent. The manufacturer shall ensure that appropriate instruction manuals, material etc. are available for the agent as well as proper training of the agent's technicians. Such suppliers shall be approved either on a case by case basis, or in accordance to the requirements of the Quality System.

3- CERTIFICATION /

Upon satisfactory completion of both the audit of the supplier and the demonstration test, as applicable, **P.M.S** will issue a Certificate of Approval stating that the supplier's service operation system has been found to be satisfactory and that the results of services performed in accordance with that system may be accepted and utilised by **P.M.S** Surveyors in making decisions affecting classification or statutory certification, as relevant. The Certificate will clearly state the type and scope of services and any limitations or restrictions imposed including type of equipment and/or names of Manufacturers of equipment where this is a limiting restraint. The supplier will also be included in **P.M.S** record of approved service suppliers.

Renewal of the Certificate is to be made at intervals not exceeding three (3) years by verification through audits that approved conditions are maintained or, where applicable, on expiry of the supplier's approval received from an equipment Manufacturer, whichever comes first. In the latter case, **P.M.S** is to be informed in due course by the Service Supplier.

4- INFORMATION REGARDING ALTERATIONS TO THE CERTIFIED SERVICE OPERATING SYSTEM /

When any alteration to the certified service operating system of the supplier is made, such alteration is to be immediately informed to **P.M.S**.

Re-audit may be required when deemed necessary by **P.M.S**.

5- CANCELLATION OF APPROVAL /

P.M.S reserves the right to cancel the approval and to inform all interested parties.

Approval may be cancelled in the following cases:

- > where the service was improperly carried out or the results were improperly reported;
- where a Surveyor finds deficiencies in the approval service operating system of the supplier and appropriate corrective action is not taken;
- where alterations have been made to the Company's Quality System relevant to the service supplier certificates, without written notification to P.M.S;
- > where wilful acts or omissions are ascertained; and
- ➤ where any deliberate misrepresentation has been made by the Service Supplier.

A supplier whose approval was cancelled, may apply for re-approval provided it has corrected the non-conformities which resulted in cancellation, and P.M.S is able to confirm it has effectively implemented the corrective action.


Expiration or cancellation of the Supplier's parent company approval automatically invalidates approval of all agents and subsidiaries if these are certified according to the requirements of the Quality System.



6- EXISTING APPROVALS /

Approvals for the categories of service suppliers granted before the date of implementation of this procedure by **P.M.S** may remain valid as stated in the respective certificates for a period up to but not exceeding 3 years.

Renewals of such certificates must be carried out in accordance with the current procedure.



PRINCIPAL TECHNICAL DEPARTMENT

Pacific Marine Services F.Z.E - Ajman Marine Classification Service Company Mail : pacific.m.s@eim.ae E-mail : technical@pmsclass.org

website : www.pmsclass.org P.O.Box: 8474 . Ajman . U.A.E







This message contains confidential information. To know more, please click on the following link: disclaimer-pms

Kind Regards,

CONTACT US





PART B/

> SPECIAL REQUIREMENTS FOR VARIOUS CATEGORIES OF SERVICE SUPPLIERS

1- FIRMS ENGAGED IN THICKNESS MEASUREMENTS ON SHIPS

EXTENT OF ENGAGEMENT.

Thickness measurement of structural material of ships except non-ESP ships less than 500 gross tonnage and all fishing vessels.

SUPERVISOR.

The responsible supervisor shall be qualified according to a recognised national or international industrial NDT standard (e.g. EN 473 level II as amended or ISO 9712 level II as amended).

OPERATORS.

The operators carrying out the measurements shall be certified to a recognised national or international industrial standard (e.g. EN 473 level I as amended or ISO 9712 level I as amended) and shall have adequate knowledge of ship structures sufficient to elect a representative position for each measurement.

EQUIPMENT.

On coated surfaces, instruments using pulsed echo technique (either with oscilloscope or digital instruments using multiple echoes, single crystal technique) are required. Single echo instruments may be used on uncoated surfaces, which have been cleaned and ground..

PROCEDURES.

Documented work procedures are at least to contain information on inspection preparation, selection and identification of test locations, surface preparation, protective coating preservation, calibration checks, and report preparation and content.

REPORTING.

The report shall be based on the guidelines given in IACS UR Z7, UR Z7.1, UR Z7.2, Z10.1, Z10.2, Z10.3, Z10.4 and Z10.5, as relevant P.M.S Rules.

VERIFICATION.

The supplier must have the Surveyor's verification of each separate job, documented in the report by the attending Surveyor(s) signature.



2- FIRMS ENGAGED IN TIGHTNESS TESTING OF CLOSING APPLIANCES SUCH AS HATCHES, DOORS ETC. WITH ULTRASONIC EQUIPMENT

EXTENT OF ENGAGEMENT.

Ultrasonic tightness testing of closing appliances such as hatches, doors etc.

OPERATORS.

The operator is to have the following qualifications:

- Have knowledge of different closing appliances such as hatches, doors etc. including their design, functioning and sealing features.
- ➤ Have experience with the operation and maintenance of different closing appliances such as hatches, doors etc.
- > Be able to document theoretical and practical training onboard in using the ultrasonic equipment specified.

It shall be demonstrated to the Surveyor that the ultrasonic equipment is fit for the purpose of detecting leakages in closing appliances.



For further information, please refer to PMS on Website of (www.pmsclass.org) - https://pmsclass.org/rules/pms-technical-publications/

Ajman Free Zone F.Z.E – P.O.BOX 8474 Ajman – Tel Fax 0097167411070-Mobil No 00971504500338 – Mail (<u>pacific.m.s@eim.ae</u>) (pacific.m.s@eim.ae) موابل رقم 00971504500338 – بريد الكتروني (8474 موابل رقم 8474 موابل رقم 00971504500338 – سريد الكتروني (عجمان المنطقة الحرة – ص.ب (8474) – فاكس 0097167411070 – موابل رقم 10971504500338



3- FIRMS CARRYING OUT IN-WATER SURVEY OF SHIPS AND MOBILE OFFSHORE UNITS.

EXTENT OF ENGAGEMENT.

In-water survey of ships and mobile offshore units by diver or Remote Operated Vehicle.

TRAINING OF PERSONNEL.

The supplier is responsible for the qualification of its divers and the diving equipment utilised when carrying out inspection. Knowledge of the following shall be documented:

- > Ship's underwater structure and appendages, tail shaft, propeller, rudder and its bearings, etc.
- Non-destructive testing in accordance with a recognised national or international industrial NDT standard This requirement only applies if an in-water survey company performs non-destructive testing.
- > Bearing clearance measurements on rudders and tail shaft.
- > Under-water video monitoring with TV-monitors on deck, as well as still picture work.
- Operation of under-water communication system.
- Special equipment and tools e.g. hull cleaners, grinders, cutters, etc.

A plan for training of personnel in the reporting system, minimum Rule requirements for relevant ship types, ship's underwater structure, measuring of bearing clearances, the recognition of corrosion damage, buckling and deteriorated coatings, etc. shall be included.

SUPERVISOR.

The supervisor shall be qualified according to the supplier's general requirements and shall have a minimum of two years' experience as a diver carrying out inspection.

DIVERS CARRYING OUT INSPECTION.

The diver carrying out the inspection shall have had at least one year's experience as an assistant diver carrying out inspections (including participation in a minimum of 10 different assignments).

EQUIPMENT.

The following shall be available:

- ➤ Closed circuit colour television with sufficient illumination equipment
- > Two-way communication between diver and surface staff.
- **▶** Video recording device connected to the closed circuit television.
- > Still photography camera.
- > Equipment for carrying out thickness gauging, non-destructive testing and measurements, e.g. clearances, indents, etc., as relevant to the work to be performed.
- **Equipment for cleaning of the hull.**
- > Remote Operated Vehicle, if applicable.



PROCEDURES AND GUIDELINES.

The supplier shall have documented operational procedures and guidelines for how to carry out the inspection and how to handle the equipment. These shall include:

- > Two-way communication between diver and surface
- **Video recording and closed circuit television operation.**
- ➤ Guidance of the diver along the hull to provide complete coverage of the parts to be inspected.
- ➤ Guidance for the operation and maintenance of the Remote Operated Vehicle, if applicable.

VERIFICATION.

The supplier must have the Surveyor's verification of each separate job, documented in the report by the attending Surveyor(s) signature..





4- FIRMS ENGAGED IN INSPECTION AND MAINTENANCE OF FIRE EXTINGUISHING EQUIPMENT AND SYSTEMS.

EXTENT OF ENGAGEMENT.

Inspections and maintenance of fire-extinguishing equipment and systems such as fixed fire extinguishing systems, portable fire extinguishers and fire detection and alarm systems.

EXTENT OF APPROVAL.

Service Suppliers are to have professional knowledge of fire theory, fire-fighting and fire-extinguishing appliances sufficient to carry out the maintenance and/or inspections, and to make the necessary evaluations of the condition of the equipment

In demonstrating professional knowledge, Service Suppliers are to have an understanding of the various types of fires and the extinguishing media to be used on them

For fixed fire-extinguishing systems, Service Suppliers are to demonstrate an understanding of the principles involved with gas, foam, deluge, sprinkler and water mist systems, as relevant for the approval being sought.

PROCEDURES.

Service Suppliers are to have documented procedures and instructions on how to carry out the servicing of the equipment and/or system. These are to either contain or make reference to the Manufacturer's servicing manuals, servicing bulletins, instructions and training manuals, as appropriate, and to international requirements.

Additionally they are to make reference to any requirements (e.g. what markings should be appended to the equipment/system)

REFERENCE DOCUMENTS.

The Service Supplier is to have access to the following documents:

- Manufacturer's servicing manuals, servicing bulletins, instructions and training manuals, as appropriate.
- > Type Approval certificates showing any conditions that may be appropriate during the servicing and/or maintenance of fire-extinguishing equipment and systems.
- ➤ SOLAS, MSC.1/Circular.1318 (Guidelines for the Maintenance and Inspections of Fixed Carbon Dioxide Fire-Extinguishing Systems), International Code for Fire Safety Systems (FSS Code), ISO 6406 (Periodic inspection and testing of seamless steel gas cylinders), and any documentation specified in the authorisation or license from the equipment manufacturer.
- MSC/Circ.670 (Guidelines for the Performance and Testing Criteria and Surveys of High Expansion Foam Concentrates for fixed Fire-Extinguishing Systems).
- > MSC/Circ.798 (Guidelines for the Performance and Testing Criteria and Surveys of Medium Expansion Foam Concentrates for fixed Fire-Extinguishing Systems).
- MSC/Circ.799 ((Guidelines for the Performance and Testing Criteria and Surveys of Expansion Foam Concentrates for fixed Fire-Extinguishing Systems of Chemical Tankers).
- ➤ MSC.1/Circ.1312 (Revised Guidelines for the Performance and Testing Criteria and Surveys of Foam Concentrates for fixed Fire-Extinguishing Systems as corrected by MSC/Circ.1312/Corr.1).
- ➤ MSC.1/Circ.1432 (Revised Guidelines for the maintenance and Inspection of Fire Protection Systems and Appliances).
- ➤ IMO Res. A. 951(23) Improved guidelines for marine portable fire extinguishers.



- ➤ MSC.1/Circ.1370 Guidelines for the design, construction and testing of fixed hydrocarbon gas detection systems.
- > Guidelines adopted by IMO for fire extinguishing equipment and systems specifically intended for service by service suppliers.

EQUIPMENT AND FACILITIES.

A. General Requirements.

If Service Suppliers undertake shore-based inspecting and maintenance, they should maintain and implement procedures for workshop cleanliness, ventilation and arrangement, with due cognisance of the spares and extinguishing media being stored, to ensure safe and effective working procedures.

Service Suppliers undertaking inspecting and maintenance of equipment and systems onboard are to provide the appropriate facilities to either complete the work onboard or remove the necessary items to their workshops.

B. Equipment.

Sufficient and appropriate spares and tools are to be available as applicable, which should include:

- > Various scales to weigh items.
- ➤ Means to hydrostatically pressure test components/systems/storage bottles.
- ➤ Liquid/gas, flow meters, as appropriate.
- Pressure gauges or manometers.
- In the cases of foam concentrates and portable fire-extinguishers, chemical analysis equipment and a testing bay, respectively; and.
- Specific equipment/spares as may be specified by Manufacturer.
- **Level measuring equipment for bottles.**
- Recharging facilities for pressurized bottles, extinguishers and cartridges.





5- FIRMS ENGAGED IN SERVICING INFLATABLE LIFERAFTS, INFLATABLE LIFEJACKETS, HYDROSTATIC RELEASE UNITS, INFLATABLE RESCUE BOATS, MARINE EVACUATION SYSTEMS..

EXTENT OF ENGAGEMENT.

- > Servicing of inflatable life rafts, inflatable lifejackets, hydrostatic release units and/or inflatable rescue boats.
- > Servicing of marine evacuation systems.

EQUIPMENT AND FACILITIES.

IMO Res. A.761(18) as amended by MSC.55(66) gives recommendations on conditions for the approval of servicing stations for inflatable life rafts which shall be observed as relevant.

Where inflatable life rafts are subject to extended service intervals, MSC.1/Circ.1328 should also be followed.

PROCEDURES AND INSTRUCTIONS.

The supplier shall have documented procedures and instructions for how to carry out service of equipment. Where inflatable liferafts are subject to extended service intervals in accordance with the requirements of SOLAS Regulation III/20.8.3, MSC.1/Circ.1328 should be followed in addition to Resolution A.761(18) as amended by MSC.55(66).

The supplier shall provide evidence that it has been authorised or licensed to service the particular makes and models of equipment for which approval is sought by the equipment's manufacturer.

REFERENCE DOCUMENTS.

The Service Supplier is to have access to the following documents:

- ➤ IMO Resolution A.761(18) Recommendation on Conditions for the Approval of Servicing Stations for Inflatable Liferafts (adopted on 4 November 1993), amended by Resolution MSC.55(66).
- ➤ IMO Resolution MSC.55(66).
- ➤ IMO MSC.1/Circ.1328 Guidelines for the Approval of Inflatable Liferafts Subject to Extended Service Intervals Not Exceeding 30 Months.
- Manufacturer's servicing manuals, servicing bulletins, instructions and training manuals, as appropriate.
- > Type Approval certificates, showing any conditions that may be appropriate during the servicing and/or maintenance of inflatable liferafts, inflatable rescue boats, inflatable lifejackets, and hydrostatic release units.
- LSA code/Chapter. IV, 1995 SOLAS Conference Resolution 4 regarding marine evacuation Systems.



6- FIRMS ENGAGED IN INSPECTIONS AND TESTING OF RADIO COMMUNICATION EQUIPMENT.

EXTENT OF ENGAGEMENT.

Surveys, inspection, testing, and/or measurement of radio equipment aboard ships or mobile offshore units for compliance with SOLAS regulations.

Annual testing of 406 MHz satellite EPIRBs for compliance with SOLAS Regulation IV/15.9.

The principles of this section also apply to Service Suppliers involved in inspection, performance testing and maintenance of Automatic Identification Systems (AIS). The Service Supplier is to be familiar with the equipment with which it will be involved, such as being a service agent for the equipment manufacturer.

REFERENCE DOCUMENTS.

The supplier shall have access to the following documents:

- ➤ SOLAS 1974 as amended
- ➤ IMO Res. A.789(19): Specification on the survey and certification functions of recognised organisations acting on behalf of the administration.
- ➤ MSC/Circ.1040/Rev.1 Guidelines on Annual Testing of 406 MHZ Satellite EPIRBs.
- ➤ MSC.1/Circ.1252 Guidelines on Annual Testing of the Automatic Identification System (AIS).
- SN/Circ.227, SN/Circ.227/Corr.1 and 245 Guidelines for the Installation of a Shipborne Automatic Identification System (AIS) and amendments thereto.
- > ITU Radio Regulations.
- > IMO Performance Standards for the equipment for which the Service Supplier is approved.
- > Flag State Administration requirements.
- Relevant parts, if any, of the Society's Rules and Guidelines.

SUPERVISOR.

The supervisor shall have a minimum two years education from a technical school, experience as inspector, and should preferably hold a General Operator's Certificate (GOC) or a GMDSS Radioelectronic Certificate (REC), recognised by the ITU, to operate or test radio transmitters. He should be aware of any local conditions for radio signal propagation, of regional radio stations and their facilities, and of the GMDSS infrastructure.

RADIO INSPECTOR.

The inspector carrying out the inspection shall have passed the internal training of the supplier in Radiotelephony, GMDSS, and initial and renewal surveys, as applicable. The inspector shall also have at least one year's technical school training or as alternative hold evidence that he followed a technical course approved by the relevant Administration, at least one year's experience as an assistant radio inspector and should preferably hold an appropriate National Radio Operators Certificate, recognised by the ITU, such as a GMDSS General Operator's Certificate (GOC) or a GMDSS Radioelectronic Certificate (REC). He should be aware of any local conditions for radio signal propagation, of regional radio stations and their facilities, and of the GMDSS infrastructure.



EQUIPMENT AND FACILITIES.

The supplier shall have the major and auxiliary equipment required for correctly performing the inspection. A record of the equipment used shall be kept. The record shall contain information on manufacturer and type of equipment, and a log of maintenance and calibrations.

A standard which is relevant to the radio equipment to be tested shall be available for the equipment and shall be cited in the inspection report.

For equipment employing software in conjunction with the testing/examination, this software shall be fully described and verified.

MINIMUM REQUIRED INSTRUMENTS.

- Equipment for measuring frequency, voltage, current and resistance
- Equipment for measuring output and reflect effect on VHF and MF/HF
- Equipment for measuring modulation on MF/HF and VHF (AM, FM, PM)
- Acid tester for checking specific gravity of lead batteries
- ➤ Tester for checking of correct output from Free-Float Satellite EPIRB
- Equipment for testing the performance of Automatic Identification Systems (AIS)

PROCEDURES AND INSTRUCTIONS.

The supplier shall have documented procedures and instructions for how to carry out testing and examination of radio equipment. Procedures and instructions for operating each item of the testing/inspection equipment shall also be kept and be available at all times.



7- FIRMS ENGAGED IN INSPECTIONS AND MAINTENANCE OF SELF-CONTAINED BREATHING APPARATUS

EXTENT OF ENGAGEMENT.

Inspections and maintenance of self-contained breathing apparatus, Emergency Escape Breathing Devices (EEBD).

EXTENT OF APPROVAL.

The supplier shall document and demonstrate that it has knowledge of the equipment and systems sufficient to carry out the inspections and testing of self-contained breathing apparatus to identify standards and to make the necessary evaluation of the condition of the equipment.

In demonstrating professional knowledge, Service Suppliers are to have an understanding of the operational requirements involved with self-contained breathing apparatus and how these are to be maintained.

Additionally, Service Suppliers are to demonstrate the necessary safety requirements applicable to such equipment.

PROCEDURES.

Service Suppliers are to have documented procedures and instructions on how to carry out the servicing of the equipment and/or system. These are to either contain or make reference to the Manufacturer's servicing manuals, servicing bulletins, instructions and training manuals, as appropriate.

Additionally they are to make reference to any requirements (e.g. what markings should be appended to the equipment/system) and how they should be applied.

REFERENCE DOCUMENTS.

The Service Supplier is to have access to the following documents:

- Manufacturers' servicing manuals, servicing bulletins, instructions and training manuals, as appropriate.
- > Type Approval certificates showing any conditions which may be appropriate during the servicing and/or maintenance of self-contained breathing apparatus.

EQUIPMENT AND FACILITIES.

A. General Requirements.

If Service Suppliers undertake shore-based inspecting and maintenance, they should maintain and implement procedures for workshop cleanliness, ventilation and arrangement, with due cognisance of the spares and pressurised bottles being stored, to ensure safe and effective working procedures.

Service Suppliers undertaking inspecting and maintenance of equipment and systems onboard are to provide the appropriate facilities to either complete the work onboard or remove the necessary items to their workshops.

B. Equipment.

Sufficient and appropriate spares and tools are to be available for repair, maintenance and servicing of self-contained breathing apparatus in accordance with the requirements of the Manufacturers.

These are to include, as required by the self-contained breathing apparatus equipment and/or systems:

- Various scales to weigh items
- ➤ Means to hydrostatically pressure test components/systems/storage bottles
- > Flow meters; and
- Pressure gauges or manometers
- > Equipment for checking air quality
- **Recharging facilities for breathing apparatus**



8- FIRMS ENGAGED IN EXAMINATION OF RO-RO SHIPS BOW, STERN, SIDE AND INNER DOORS.

EXTENT OF ENGAGEMENT.

Inspection of securing and locking devices, hydraulic operating system, electric control system for the hydraulics, electric indicator systems, and supporting, securing and locking devices and tightness testing.

The supplier is to be certified to the most current version of ISO 9000 series.

SUPERVISION.

In addition to General Required Supervision, the requirement to have had a minimum of two years' experience as operator/technician/inspector within the activity, a Supervisor is to have a minimum two years related education from a technical school.

TRAINING OF PERSONNEL.

Operators carrying out Non-Destructive Examination (NDE) are to be qualified to a recognised National or International Standard for the methods used.

REFERENCE DOCUMENTS.

The supplier shall have access to the following reference documents:

- > IMO International Convention on the Safety of Life at Sea (SOLAS) 74/78, as amended.
- > ISO 9002:1994 Quality systems Model for quality assurance in production, installation and servicing.
- ➤ IACS UR Z24 Survey Requirements for Shell and Inner Doors of Ro-Ro ships, or its equivalent, by the relevant class society.

REFERENCE DOCUMENTS.

- . For Inspection of Supporting Securing and Locking Devices, Hinges and Bearings :
- Equipment for measuring clearances (i.e. feeler gauges, vernier calipers, micrometers).
- Non-destructive examination (i.e. dye penetrant, magnetic particle inspection).
 - . For Tightness Testing:
- > Ultrasonic leak detector or equivalent.
 - . For Inspection of Hydraulic Operating System:
- > Pressure gauges.
- Particle counter for analysing the quality of hydraulic fluid.
 - . For Inspection of Electric Control System and Indication System :
- Digital multi-meter
- > Earth fault detector

PROCEDURES AND INSTRUCTIONS.

The supplier shall have access to drawings and documents, including the Operating and Inspection Manual. The supplier shall have access to the service history of the doors.

The supplier should use, complete and sign a checklist which has been found acceptable by the classification society.



9- FIRMS ENGAGED IN ANNUAL PERFORMANCE TESTING OF VOYAGE DATA RECORDERS (VDR) AND SIMPLIFIED VOYAGE DATA RECORDERS (S-VDR).

EXTENT OF ENGAGEMENT.

Testing and servicing of Voyage Data Recorders (VDR) and Simplified Voyage Data Recorders (S-VDR) in accordance with SOLAS Chapter V Regulation 18.8 and IMO - MSC.1/Circular.1222 - Guidelines on Annual Testing of Voyage Data Recorders (VDR) and Simplified Voyage Data Recorders (S-VDR), as applicable.

EXTENT OF APPROVAL.

The supplier shall provide evidence that he has been authorised or licensed by the equipment's manufacturer to service the particular makes and models of equipment for which approval is sought.

Where the Service Supplier is also the Manufacturer of the Voyage Data Recorder (VDR) or Simplified Voyage Data Recorder (S-VDR) and has elected to apply IMO - MSC.1/Circular.1222 - Guidelines on Annual Testing of Voyage Data Recorders (VDR) and Simplified Voyage Data Recorders (S-VDR) in its entirety for the purpose of acting as a Service Supplier engaged in annual performance testing, the following is to apply:

- ➤ The Manufacturer is responsible for appointing Manufacturer's Authorised Service Stations to carry out annual performance testing.
- ➤ The Manufacturer is required to be an Approved Service Supplier and is to satisfy the requirements for Service Suppliers engaged in annual performance testing of Voyage Data Recorders (VDR) and Simplified Voyage Data Recorders (S-VDR), as applicable.
- ➤ The Manufacturer's Authorised Service Station is not required to be an Approved Service Supplier.
- The Manufacturer is to demonstrate that IMO MSC.1/Circular.1222 Guidelines on Annual Testing of Voyage Data Recorders (VDR) and Simplified Voyage Data Recorders (S-VDR) is applied in its entirety.

PROCEDURES.

The Service Supplier shall have documented procedures and instructions.

Where the Service Supplier is also the Manufacturer of the Voyage Data Recorder (VDR) or Simplified Voyage Data Recorder (S-VDR) and has selected to apply IMO - MSC.1/Circular.1222 - Guidelines on Annual Testing of Voyage Data Recorders (VDR) and Simplified Voyage Data Recorders (S-VDR) in its entirety for the purpose of acting as a Service Supplier engaged in annual performance testing, the following is to apply:

- 1. The Manufacturer is to have documented procedures for the assessment and authorisation of Manufacturer's Authorised Service Stations who carry out annual performance testing.
- 2. The Manufacturer is to have documented procedures for the review of Manufacturer's Authorised Service Stations annual performance test reports, analysis of the Voyage Data Recorder (VDR) and Simplified Voyage Data Recorder (S-VDR) 12 hour log and the issue of annual performance test certificates to the Owner/Operator.
- **3.** The Manufacturer is to maintain a list of Manufacturer's Authorised Service Stations that can be accessed (by any available means, e.g. via a nominated contact point or from the Manufacturer's website) upon request.



REFERENCE DOCUMENTS.

The Service Supplier is to have access to the following documents:

- ➤ IMO International Convention on the Safety of Life at Sea (SOLAS), 74/78, Ch V, Reg 18.8. Approval, surveys and performance standards of navigational systems and equipment and voyage data recorder.
- ➤ IMO MSC.1/Circular.1222 Guidelines on Annual Testing of Voyage Data Recorders (VDR) and Simplified Voyage Data Recorders (S-VDR) (11 December 2006).
- ➤ IMO Resolution A.861(20) (adopted on 27 November 1997) as amended by IMO Resolution MSC.214(81) and revised by IMO Resolution MSC.333(90) Performance Standards for Shipborne Voyage Data Recorders (VDRs).
- ➤ IMO Resolution MSC.163(78) Performance Standards for Shipborne Simplified Voyage Data Recorders (S-VDRs) (adopted on 17 May 2004), as amended by IMO Resolution 214(81).

The Service Supplier is to have access to applicable industry performance standards, e.g.:

- ➤ IEC 61996 Maritime navigation and radiocommunication equipment and systems Shipborne voyage data recorder (VDR).
- ➤ IEC 61996–2 Maritime navigation and radio communication equipment and systems Shipborne voyage data recorder (VDR) Part 2: Simplified voyage data recorded (SVDR) Performance requirements, method of testing and required test results.

The Service Supplier is also to have access to any documentation specified in the authorisation or license from the equipment manufacturer.

EQUIPMENT AND FACILITIES.

In addition, the Service Supplier shall have equipment as specified in the authorisation or license from the equipment Manufacturer.

REPORTING - TEST REPORT.

The Service Supplier shall issue a certificate of compliance as specified in the International Convention on Safety of Life at Sea (SOLAS 1974), as amended, Ch V, Reg 18.8.

Annual Performance Test of VDR and S-VDR should be recorded in the form of the model test report given in the Appendix to MSC.1/Circular.1222, signed and stamped by the Service Supplier and attached to the annual performance test certificate.

Where the Service Supplier is also the Manufacturer of the Voyage Data Recorder (VDR) or Simplified Voyage Data Recorder (S-VDR) and has selected to apply IMO - MSC.1/Circular.1222 - Guidelines on Annual Testing of Voyage Data Recorders (VDR) and Simplified Voyage Data Recorders (S-VDR) in its entirety for the purpose of acting as a Service Supplier engaged in annual performance testing, the Manufacturer is to make arrangements for the following:

- > Review of the Manufacturer's Authorised Service Station annual performance test report.
- Analysis of the recorder's 12 hour log.
- ➤ Checking of the master record/database for the recorder.

Issue of the annual performance test certificate to the Owner/Operator within 45 days of completion of the annual performance test.



10- FIRMS ENGAGED IN INSPECTIONS OF LOW LOCATION LIGHTING SYSTEMS USING PHOTO LUMINESCENT MATERIALS AND EVACUATION GUIDANCE SYSTEMS USED AS AN ALTERNATIVE TO LOW LOCATION LIGHTING SYSTEMS.

EXTENT OF ENGAGEMENT.

Luminance measurements on board ships of low location lighting systems using photo luminescent materials.

OPERATORS.

The operator is to have the following qualifications:

- Have adequate knowledge of the applicable international requirements (namely SOLAS reg. II-2/13.3.2.5, IMO Res. A.752(18) - Guidelines for the Evaluation, Testing and Application of Low-Location Lighting on Passenger Ships, ISO 15370-2010, FSSS Code Chapter 11).
- Be able to document theoretical and practical training on board in using equipment specified.

EQUIPMENT.

The measuring instrument shall incorporate a fast-response photometer head with CIE (International Commission on Illumination) photopic correction and have a measurement range of at least 10-4 cd/m2 to 10 cd/m2.

PROCEDURES.

Documented work procedures are at least to contain information on inspection preparation, selection and identification of test locations.

REPORTING.

The report shall conform to Annex C of ISO 15370-2010.

VERIFICATION.

The supplier must have the Surveyor's verification of each separate job, documented in the report by the attending Surveyor's signature.

REFERENCE DOCUMENTS.

The Service Supplier is to have access to the following documents:

- ➤ IMO International Convention on the Safety of Life at Sea (SOLAS), 74/78 Ch II-2, Pt D, Reg 13.3.2.5 Marking of escape routes.
- ➤ IMO Fire Safety Systems (FSS Code), Ch 11 Low-location lighting systems.
- ➤ IMO Resolution A.752(18) Guidelines for the Evaluation, Testing and Application of Low-Location Lighting on Passenger Ships (adopted on 4 November 1993).
- ➤ ISO 15370:2010 Ships and marine technology Low-location lighting on passenger ships Arrangement.
- ➤ MSC/Circ.1168 Interim guidelines for the testing, approval and maintenance of evacuation guidance systems used as an alternative to low-location lighting systems.



11- FIRMS ENGAGED IN SOUND PRESSURE LEVEL MEASUREMENTS OF PUBLIC ADDRESS AND GENERAL ALARM SYSTEMS ON BOARD SHIPS.

EXTENT OF ENGAGEMENT.

Sound pressure level measurements of public address and general alarm systems on board ships.

OPERATORS.

The operator is to have the following qualifications:

- ➤ Have adequate knowledge of the applicable international requirements (SOLAS Reg. III/4 and III/6, LSA CODE Chapter VII/7.2, IMO Code on alarms and indicators, 1995).
- Be able to document theoretical and practical training onboard in using equipment specified.

EQUIPMENT.

The measuring instrument shall be an integrating sound level meter with frequency analyser capabilities complying with IEC (International Electrotechnical Commission) 60651 and IEC 61672, type 1 precision class with, at least an A-weighting frequency response curve and 1/3 octave and 1 octave band filters, complying to IEC 61260, as appropriate for the measurements to be carried out. In addition microphones shall be of the random incidence type, complying with IEC 60651.

PROCEDURES.

Documented work procedures are at least to contain information on inspection preparation, calibration, selection and identification of test locations.

REPORTING.

The report shall describe, as a minimum, the environmental conditions of the tests and, for each test location, the ambient noise level or the speech interference level, as appropriate for the measurements to be carried out. The report shall conform to any other specific requirement of **P.M.S.**

VERIFICATION.

The supplier must have the Surveyor's verification of each separate job, documented in the report by his signature.

REFERENCE DOCUMENTS.

The Service Supplier is to have access to the following documents:

- ➤ SOLAS 74/78, Ch III, Pt A, Reg 4 Evaluation, testing and approval of life-saving appliances and arrangements.
- ➤ SOLAS 74/78, Ch III, Pt B, Reg 6 Communications.
- ➤ International Life-Saving Appliance (LSA) Code, Ch VII, Reg 7.2 General alarm and public address system.
- > IMO Code on Alarms and Indicators, 1995 as amended.
- ➤ IEC 60651 (2001-10) Sound level meters.
- ➤ IEC 61672 Electroacoustics Sound level meters.
- ➤ IEC 61260 Electroacoustics Octave-band and fractional-octave-band filters.



12- FIRMS ENGAGED IN TESTING OF COATING SYSTEMS IN ACCORDANCE WITH IMO RESOLUTION MSC.215(82) AS AMENDED AND IACS UI SC223 AND/OR MSC.288(87) AS AMENDED.

EXTENT OF ENGAGEMENT.

Testing of coatings systems according to IMO Resolution MSC.215(82), as corrected by IMO MSC.1/Circ.1381 and amended by IMO Resolution 341(91) and IACS UI SC223 and/or MSC.288(87), as corrected by IMO MSC.1/Circ.1381 and amended by IMO Resolution 341(91).

LABORATORIES.

The laboratory is to provide to the P.MS the following information:

- A detailed list of the Laboratory test equipment for the coating approval according to the IMO Resolution MSC.215(82) as amended and/or MSC.288(87) as amended.
- A detailed list of reference documents comprising a minimum those referred to in IMO Resolution MSC.215(82) as amended and/or MSC.288(87) as amended for the coating approval.
- > Details of test panel preparation, procedure of test panel identification, coating application, test procedures and a sample test report.
- > Details of exposure method and site for weathering primed test panels.
- A sample daily or weekly log/form for recording test conditions and observations including unforeseen interruption of the exposure cycle with corrective actions.
- ➤ Details of any sub-contracting agreements (if applicable).
- ➤ Comparison test report with an approved coating system or laboratory if available.

REPORTING.

Reference is made to the following IACS Recommendations:

- Rec. 101: IACS Model Report for IMO Resolution MSC.215(82) Annex 1 "Test Procedures for Coating Qualification".
- Rec. 102: IACS Model Report for IMO Resolution MSC.215(82) Annex 1 "Test.
- ➤ Procedures for Coating Qualification", Section 1.7 Crossover Test.

Audit of the test laboratory is to be based on this procedure and the standards listed in the IMO Resolution MSC.215(82) as amended and/or MSC.288(87) as amended for the coating approval.



13- FIRMS ENGAGED IN THE SERVICING AND MAINTENANCE OF LIFEBOATS, LAUNCHING APPLIANCES, ON-LOAD RELEASE GEAR AND DAVIT-LAUNCHED LIFERAFT AUTOMATIC RELEASE HOOKS.

EXTENT OF ENGAGEMENT.

Servicing and maintenance of lifeboats, launching appliances, on-load release gear and davit-launched liferaft automatic release hooks.

EXTENT OF APPROVAL.

The contents of this procedure apply equally to manufacturers when they are acting as Service Suppliers.

Any Service Supplier engaged in the thorough examination, operational testing, repair and overhaul of lifeboats, launching appliances, on-load release gear and davit-launched liferaft automatic release hooks carried out in accordance with SOLAS regulation III/20 should be qualified in these operations for each make and type of equipment for which they provide the service, and provide manufacturers documentary evidence that they have been so authorized or they are certified in accordance with an established system for training and authorization in accordance with MSC.1/Circ.1277, as amended.

In cases where an equipment manufacturer is no longer in business or no longer provides technical support, Service Suppliers may be authorised for the equipment on the basis of prior authorization for the equipment and/or long term experience and demonstrated expertise as an authorized service provider.

QUALIFICATIONS AND TRAINING OF PERSONNEL.

Service Suppliers should be trained and qualified in the operations for which they are authorised, for each make and type of equipment for which they provide the service. Such training and qualification should include, as a minimum:

- 1- Employment and documentation of personnel certified in accordance with a recognized national, international or industry standard as applicable, or an equipment manufacturer's established certification program. In either case, the certification program should be based on the guidelines in the appendix for each make and type of equipment for which service is to be provided.
- 2- The education and training for initial certification of personnel should be documented and address, as a minimum:
- > Causes of lifeboat accidents.
- ➤ Relevant rules and regulations, including International Conventions.
- > Design and construction of lifeboats, including on-load release gear and launching appliances.
- Education and practical training in the procedures specified in annex 1 of MSC.1/Circ.1206/Rev.1 for which certification is sought.
- > Detailed procedures for thorough examination, operational testing, repair and overhaul of lifeboats, launching appliances and on-load release gear, as applicable; and.
- ➤ Procedures for issuing a report of service and statement of fitness for purpose based on MSC.1/Circ.1206/Rev.1 (annex 1, paragraph 15).



- 3- The education and training for the personnel should include practical technical training on actual inspection and maintenance using the equipment (lifeboats, launching appliances and/or on-load release gear) for which the personnel are to be certified. The technical training should include disassembly, reassembly, correct operation and adjustment of the equipment. Classroom training should be supplemented by field experience in the operations for which certification is sought, under the supervision of an experienced senior certified person.
- 4- At the time of initial certification and at each renewal of certification, the service supplier shall provide documentation to verify personnel's satisfactory completion of a competency assessment using the equipment for which the personnel are certified.
- 5- The Service Supplier shall require refresher training as appropriate to renew the certification.

REFERENCE DOCUMENTS.

The Service Supplier is to have access to the following documents:

- > IMO MSC.1/Circ.1206/Rev.1, as amended, Measures to Prevent Accidents with Lifeboats.
- ➤ IMO MSC.1/Circ.1277, as amended, Interim Recommendation on Conditions for Authorization of Service Providers for Lifeboats, Launching Appliances and On-Load Release Gear.
- ➤ IMO Resolution A.689(17), recommendation on testing of life-saving appliances and, for life-saving appliances installed on board on or after 1 July 1999, Resolution MSC.81(70), revised recommendation on testing of life-saving appliances.
- For servicing and repair work involving disassembly or adjustment of on-load release mechanisms, availability of the equipment manufacturer's specifications and instructions.
- > Type Approval certificate showing any conditions that may be appropriate during the servicing and/or maintenance of lifeboats, launching appliances and on-load release gear.

EQUIPMENT AND FACILITIES.

The Service Supplier is to have access to the following:

- > Sufficient tools, and in particular any specialized tools specified in the equipment manufacturer's instructions, including portable tools as needed for work to be carried out on board ship.
- Access to sufficient materials, spare parts and accessories as specified by the equipment manufacturer for repairing lifeboats, launching appliances and on-load release gear, as applicable.
- For servicing and repair work involving disassembly or adjustment of on-load release mechanisms, availability of genuine replacement parts as specified or supplied by the equipment manufacturer.

REPORTING.

The report should conform to the requirements of MSC.1/Circ.1206/Rev.1 (annex 1, paragraph 15). When repairs, thorough examinations and annual servicing are completed, a statement confirming that the lifeboat arrangements remain fit for purpose should be promptly issued by the Service Supplier.



14- FIRMS ENGAGED IN MEASUREMENTS OF NOISE LEVEL ONBOARD SHIPS.

EXTENT OF ENGAGEMENT.

Sound pressure level measurements onboard Ship.

SUPERVISOR.

The supervisor shall have a minimum of 2 years of experience as an operator in sound pressure level measurements..

OPERATORS.

The operator is to have the following qualifications:

- ➤ Knowledge in the field of noise, sound measurements and handling of measurement equipment.
- Adequate knowledge of the applicable international requirements (SOLAS Regulation II-1/3-12, as amended, and IMO Code on noise levels onboard Ships, as amended,).
- At least 1 years' experience, including participation in a minimum of 5 measurement campaigns as an assistant operator.
- Training concerning the procedures specified in IMO Code on Noise Levels onboard Ships.
- > Be able to document theoretical and practical training onboard in using a sound level meter.

EQUIPMENT.

1- Sound level meters.

Measurement of sound pressure levels shall be carried out using precision integrating sound level meters. Such meters shall be manufactured to IEC 61672-1(2002-05)¹, as amended, type/class¹ standard as applicable, or to an equivalent standard acceptable to the Administration².

- ¹ Recommendation for sound level meters.
- ² Sound level meters class/type 1 manufactured according to IEC 651/IEC 804 may be used until 1 July 2016.
- 2- Octave filter set.

When used alone, or in conjunction with a sound level meter, as appropriate, an octave filter set shall conform to IEC 61260 (1995)3, as amended, or an equivalent standard acceptable to the Administration.

³ Octave-band and fractional-octave-band filters.

3- Sound Calibrator.

Sound calibrators shall comply with the standard IEC 60942 (2003-01), as amended, and shall be approved by the manufacturer of the sound level meter used.

4- Calibration.

Sound Calibrator and sound level meter shall be verified at least every two years by a national Standard laboratory or a competent laboratory accredited according to ISO 17025 (2005), as amended. A record with a complete description of the equipment used shall be kept, including a calibration log.



5- Microphone wind screen.

A microphone wind screen shall be used when taking readings outside, e.g. on navigating bridge wings or on deck, and below deck where there is any substantial air movement. The wind screen should not affect the measurement level of similar sounds by more than 0.5 dB(A) in "no wind" conditions.

PROCEDURES AND INSTRUCTIONS.

The supplier shall have documented procedures and instructions to carry out service of the equipment. Documented work procedures are at least to contain information on inspection preparation, selection and identification of sound level measurement locations, calibration checks and report preparation.

The supplier shall have access to the following documents:

- ➤ SOLAS 1988, as amended (Reg.II-1/3-12).
- Resolution A.468(XII) and IMO Resolution MSC.337(91) code on noise levels on board ships.
- Resolution A.343(IX) Recommendation on methods of measuring noise levels at listening posts.
- ➤ The Society's Rules and Guidelines.

REPORTING.

A noise inspection report shall be made for each ship. The report shall comprise information on the noise levels in the various spaces on board. The report shall show the reading at each specified measuring point. The points shall be marked on a general arrangement plan, or on accommodation drawings attached to the report, or shall otherwise be identified. The format for noise inspection reports is set out in appendix 1 of IMO Code on Noise Levels onboard Ships and may conform to any other specific requirement of the society (refer to IMO circular MSC.337(91)).

VERIFICATION.

The supplier must have the Surveyor's verification of each separate job, documented in the report by his signature.



15- FIRMS ENGAGED IN TIGHTNESS TESTING OF PRIMARY AND SECONDARY BARRIERS OF GAS CARRIERS WITH MEMBRANE CARGO CONTAINMENT SYSTEMS FOR VESSELS IN SERVICE.

EXTENT OF ENGAGEMENT.

Firms carrying out the following:

- Global Vacuum Testing of Primary and Secondary Barriers.
- Acoustic Emission (AE) Testing.
- > Thermographic Testing.

REQUIREMENTS FOR FIRMS ENGAGED IN GLOBAL TESTING OF PRIMARY AND SECONDARY BARRIERS.

1. Testing Procedures.

Testing is to be carried out in accordance with cargo containment system designer's procedures as approved by the society.

2. Authorization.

The supplier is to be authorized by the system designer to carry out the testing.

3. Equipment.

Equipment is to be maintained and calibrated in accordance with recognized national or international industrial standards.

4. Reporting.

The report is to contain the following:

- Date of testing.
- ➤ Identity of test personnel.
- > Vacuum decay data for each.
- > Summary of test results.

REQUIREMENTS FOR FIRMS ENGAGED IN ACOUSTIC EMISSION (AE) TESTING.

1. Testing Procedures.

The supplier is to have documented procedures based upon recognized national or international industrial standards to perform ultrasonic leak test using AE sensors for the secondary barrier of membrane cargo containment systems. The procedures are to include details of personnel responsibilities and qualification, instrumentation, test preparation, test method, signal processing, evaluation and reporting.

Note: The differential pressure during testing should not exceed the containment system designer's limitations.

2. Supervisor.

The responsible supervisor shall be certified to a recognized national or international industrial standard (e.g. Level II, ISO-9712 as amended or SNT-TC-1A as amended) and have one year experience at Level II.

3. Operators.

The operators carrying out the acoustic emission (AE) testing shall be certified to a recognized national or international industrial standard (e.g. Level I, ISO-9712 as amended or SNT-TC-1A as amended) and shall have adequate knowledge of ship structures sufficient to determine sensor placement.



4. Equipment.

Equipment is to be maintained and calibrated in accordance with recognized national or international industrial standards or equipment manufacturer's recommendations.

5. Evaluation of acoustic emission (AE) testing.

Must be carried out by the supervisor or individuals certified to a recognized national or international industrial standard (e.g. Level II, ISO-9712 as amended or SNT-TC-1A as amended) and have one year experience at Level II.

6. Reporting.

The report is to contain the following:

- > Date of testing.
- > Supervisor and operator(s) certifications.
- > Description of time and pressure of each cycle of test.
- List and sketch detailing location of possible defects.

REQUIREMENTS FOR FIRMS ENGAGED IN THERMOGRAPHIC TESTING.

1. Testing Procedures.

Testing is to be carried out in accordance with the cargo containment system designer's procedures as approved by the society.

2. Authorization

The supplier is to be authorized by the system designer to carry out the testing.

3. Supervisor.

The responsible supervisor shall be certified to a recognised national or international industrial standard (e.g. Level II, ISO-9712 as amended or SNT-TC-1A as amended) with additional certification in infrared/thermal testing. Certification by the supplier is not allowed and must be obtained through an independent certification body.

4. Operators.

The operators carrying out the imaging shall be certified to a recognized national or international industrial standard (e.g. Level I, ISO-9712 as amended or SNT-TC- 1A as amended) with additional certification in infrared/thermal testing and shall have adequate knowledge of ship structures sufficient to determine position for each identified image, and of the containment system to understand the basis of the testing. Certification by the supplier is not allowed and must be obtained through an independent certification body.

5. Equipment.

Thermal cameras and sensors are to be in accordance with the system designer's procedures with regards to sensitivity, accuracy and resolution.

Equipment are to be in accordance with recognized standard (IEC, etc.) with regards their safety characteristics for the use in hazardous areas (in gas explosive atmosphere), maintained and calibrated in accordance with the maker's recommendations.

6. Evaluation of thermographic images

Must be carried out by the supervisor or individuals certified to a recognized national or international industrial standard (e.g. Level II, ISO-9712 as amended or SNT-TC-1A as amended) with additional certification in infrared/thermal testing. Certification by the supplier is not allowed and must be obtained through an independent certification body.



7. Reporting.

The report is to contain the following:

- > Date of testing.
- Supervisor and operator(s) certifications.
- Differential pressures of all phases.
- List and sketch detailing location of thermal indications.
- > Thermographic images of all phases of testing for thermal indications.
- > Evaluation of thermal images indicating possible leaks.

THE RESPONSIBILITIES ON

> Ship Managers/Operators/firms providing services, should be ensure that the on ships board maintenance program to take into consideration the requirements outlined in above.

Recommendation to Owners / Managers / Operators

In order to assist firms providing services to ensure that vessel are in compliance, that the PMS has prepared a Procedure for the approval requirements with all items may be checked during auditing inspection. in order to help firms that they like to get approval by classification society of Pacific Marine Services.







Kind Regards,

CONTACT US

