



PACIFIC MARINE SERVICES

Date :13-02-2018

No .P.M.S/C038/18

CIRCULAR

Page No (2)

Amendments to the Guidelines for evaluation and replacement of lifeboat release and retrieval systems

Notice to :

Ship Owners / Manager / operators / Surveyors

With a view to include a method of assessment for backing plates and bolts not made of material resistant to corrosion in the marine environment in order to confirm their condition, the Maritime Safety Committee approved amendments to the guidelines for evaluation and replacement of lifeboat release and retrieval systems.

Dear Sirs,

Through MSC.1/Circ.1584, the Maritime Safety Committee, at its ninety-eighth session approved amendments to the Guidelines for evaluation and replacement of lifeboat release and retrieval systems (MSC.1/Circ.1392), prepared by the Sub-Committee on Ship Systems and Equipment.

The amendments.

The Administration, or a Recognized Organization acting on its behalf, may allow that hook fixed structural connections of the release mechanism and supporting structure which are not made of material resistant to corrosion in the marine environment, as required by paragraph 4.4.7.6.9 of the LSA Code, **not to be replaced if they are in a good condition and installed in a sheltered position inside the lifeboat.**

The assessment for verifying that fixed structural connections and supporting structures are in "good condition" **should be carried out by the manufacturer** or by one of its representatives in accordance with paragraph 23 of the MSC.1/Circ.1392.

The assessment for verification is not required if the materials of the foundation, bolts and supporting structure, both internally and externally, are made of materials resistant to corrosion in the marine environment.

Method of assessment

The assessment of fixed structural connections of the release mechanism and supporting structures should be carried out according to the manual developed by the manufacturer.

However, if either such a manual or the original equipment manufacturer, or any entity which has taken legal and legitimate responsibilities for equipment when the original equipment manufacturer no longer exists or supports the equipment, do not exist, this assessment should be carried out according to the following method : -

- 1- 100% visual examination of all components within clear sight in order to assess the general condition and look for signs of corrosion. No dismantling or removal of components is required at this stage.
- 2- At least 25% of bolts for each hook fixation should be removed for visual examination¹. Additionally, a non-destructive testing (NDT) technique, such as magnetic particle inspection (MPI), where suitable, may be applied. If any of the removed bolts of the hook fixation shows signs of corrosion or are deemed to be in "bad condition", then the rest of the bolts for the same hook fixation should be removed and examined. As a general rule, any bolt that has lost material to corrosion of 2% from the original dimensions should be deemed to be "in bad condition" and replaced. Replacement bolts are to be made of material corrosion resistant in the marine environment based on a like for like principle.

For further information, please refer to PMS Circulars on Website of (www.pmsclass.org/circulars)



PACIFIC MARINE SERVICES

- 3- If fixed structural connections of the release mechanism or supporting structures show signs of corrosion, then ultrasonic thickness measurement and corrosion mapping should be performed. For this non-destructive examination (NDE) to be possible, the probes need to have adequate access and the surface needs to be smooth and appropriate for ultrasonic scanning. As a general rule, a backing plate that has suffered corrosion wastage of 10% or more from the original plate thickness should be deemed to be "in bad condition" and replaced. Replacement of structural connections, backing plates, etc. are to be made of materials resistant to corrosion in the marine environment and based on a like for like principle.
- 4- If after the assessment, the bolts, backing plates, keel shoes, etc. are in good condition, then all parts are to be cleaned and recoated, if necessary.

Backing plates and bolts installed outside the lifeboat and deemed to be in "good condition" after the assessment need not be replaced even when not made of material resistant to corrosion in the marine environment.

The full amendments on MSC.1/Circ.1584 can be found with the below.

ACT NOW

Ship Owners/Managers/Operators must take into consideration above amendments as guidance when applying SOLAS Regulation III/1.5, as adopted by resolution MSC.317(89).

Kind Regards,

You can download P.M.S Technical Publication concerning the requirements for maintenance and inspection of Fire fighting, lifesaving and radio equipment as well as drills as per statutory instruments on Website of (www.pmsclass.org) – (<https://pmsclass.org/rules/pms-technical-publications>), for further information.

For further information, please refer to PMS Circulars on Website of (www.pmsclass.org/circulars)

CONTACT US



Ajman Free Zone F.Z.E – P.O.BOX 8474 Ajman – Tel Fax 0097167411070-Mobil No 00971504500338 – Mail (pacific.m.s@eim.ae)
(pacific.m.s@eim.ae) الإلكتروني – 00971504500338 رقم موبايل – 0097167411070 فاكس (8474) – ص.ب (8474) عجمان المنطقة الحرة –

4 ALBERT EMBANKMENT
LONDON SE1 7SR
Telephone: +44 (0)20 7735 7611 Fax: +44 (0)20 7587 3210

MSC.1/Circ.1584
20 June 2017

**AMENDMENTS TO THE GUIDELINES FOR EVALUATION AND REPLACEMENT OF
LIFEBOAT RELEASE AND RETRIEVAL SYSTEMS (MSC.1/CIRC.1392)**

1 The Maritime Safety Committee, at its ninety-eighth session (7 to 16 June 2017), with a view to including a method of assessment for backing plates and bolts not made of material resistant to corrosion in the marine environment in order to confirm their condition, approved amendments to the *Guidelines for evaluation and replacement of lifeboat release and retrieval systems* (MSC.1/Circ.1392), prepared by the Sub-Committee on Ship Systems and Equipment, at its fourth session (20 to 24 March 2017), as set out in the annex.

2 Member States are invited to use the Guidelines in conjunction with the annexed amendments as guidance when applying SOLAS regulation III/1.5, as adopted by resolution MSC.317(89), and to bring the amendments to the attention of all parties concerned.

ANNEX

AMENDMENTS TO THE GUIDELINES FOR EVALUATION AND REPLACEMENT OF LIFEBOAT RELEASE AND RETRIEVAL SYSTEMS (MSC.1/CIRC.1392)

Paragraph 21 is replaced with the following:

"21 The Administration, or a recognized organization acting on its behalf, may allow that hook fixed structural connections of the release mechanism and supporting structure which are not made of material resistant to corrosion in the marine environment, as required by paragraph 4.4.7.6.9 of the LSA Code, need not be replaced if they are in a good condition and installed in a sheltered position inside the lifeboat. The assessment for verifying that fixed structural connections and supporting structures are in 'good condition' should be carried out by the manufacturer or by one of its representatives in accordance with paragraph 23 below.

The assessment for verification is not required if the materials of the foundation, bolts and supporting structure, both internally and externally, are made of materials resistant to corrosion in the marine environment.

.1 Method of assessment:

The assessment of fixed structural connections of the release mechanism and supporting structures should be carried out according to the manual developed by the manufacturer. However, if either such a manual or the original equipment manufacturer, or any entity which has taken legal and legitimate responsibilities for equipment when the original equipment manufacturer no longer exists or supports the equipment, do not exist, this assessment should be carried out according to the following method:

- .1 100% visual examination of all components within clear sight in order to assess the general condition and look for signs of corrosion. No dismantling or removal of components is required at this stage.
- .2 At least 25% of bolts for each hook fixation should be removed for visual examination¹. Additionally, a non-destructive testing (NDT) technique, such as magnetic particle inspection (MPI), where suitable, may be applied. If any of the removed bolts of the hook fixation shows signs of corrosion or are deemed to be in "bad condition", then the rest of the bolts for the same hook fixation should be removed and examined. As a general rule, any bolt that has lost material to corrosion of 2% from the original dimensions should be deemed to be "in bad condition" and replaced. Replacement bolts are to be made of material corrosion resistant in the marine environment based on a like for like principle.

¹ In most types of lifeboats, the arrangement of keel shoe fixation allows for access and removal of bolts for inspection. When this is not the case, e.g. where bolts are solidly embedded or built in to the fiber reinforced plastic (FRP) structure, the Administration, or recognized organization acting on its behalf, should handle it on a case-by-case basis.

- .3 If fixed structural connections of the release mechanism or supporting structures show signs of corrosion, then ultrasonic thickness measurement and corrosion mapping should be performed. For this non-destructive examination (NDE) to be possible, the probes need to have adequate access and the surface needs to be smooth and appropriate for ultrasonic scanning. As a general rule, a backing plate that has suffered corrosion wastage of 10% or more from the original plate thickness should be deemed to be "in bad condition" and replaced. Replacement of structural connections, backing plates, etc. are to be made of materials resistant to corrosion in the marine environment and based on a like for like principle.
- .4 If after the assessment, the bolts, backing plates, keel shoes, etc. are in good condition, then all parts are to be cleaned and recoated, if necessary.
- .2 Backing plates and bolts installed outside the lifeboat and deemed to be in 'good condition' after the assessment need not be replaced even when not made of material resistant to corrosion in the marine environment."